



MTS10

10-Inch Full Range Loudspeaker System

Professional Series

Key Features:

- ▶ 10" custom LF driver featuring high-power handling and extended low frequency response
- ▶ JBL patent compression HF driver for warm vocal reproduction in great detail
- ▶ Enclosure constructed of 15 mm MDF with durable painting
- ▶ 70° × 100° coverage pattern with smooth response on and off axis
- ▶ 18-gauge steel front grille for protection of internal components
- ▶ 35 mm pole-mount socket



Applications:

- ▶ Karaoke sound reinforcement
- ▶ For use with a sub-woofer

MTS10 is a professional-grade 10" (254 mm) two-way speaker system designed for karaoke rooms. The two-way speaker combines a custom-made 10" woofer with a patent JBL 2414H-C compression driver, and stands itself out for high power handling, large dynamic, warm vocal ranges and extended low bands. Its 70° × 100° coverage pattern provides smooth and even coverage whether installed in vertical or horizontal orientation.

MTS10 is designed in a low profile and can easily blend into any karaoke rooms. The rugged enclosure is constructed of 15 mm high quality MDF and finished in a durable coating. The front grille is made from 18-gauge steel and backed with acoustic fabrics for protection of drivers and components inside. A Neutrik® Speakon® NL4MP connector is provided for reliable connection with a professional amplifier. To meet different installation requirements, three (3) pairs of M10 threaded suspension points and a 35 mm pole-mount socket are made available.

Specifications:

System:

System Type:	10", 2-way, bass-reflex
Frequency Range (-10 dB) ¹ :	50 Hz - 20 kHz
Frequency Response (±3 dB) ¹ :	85 Hz - 18 kHz
Sensitivity (1w@1m) ¹ :	94 dB
Nominal Impedance:	8 Ohms
Maximum SPL ² :	119 dB (125 dB peak)
Power Rating ³ : (Continuous/Program/Peak)	300 W/600 W/1200 W
Coverage Pattern:	70° × 100° (H × V)

Physical:

Dimensions (H × W × D):	524 mm × 297 mm × 320 mm 20.6 inch × 11.7 inch × 12.6 inch
Net Weight:	14.2 Kg (31.3 lbs)
LF Driver:	1 × 10" (254 mm) woofer
HF Driver:	1 × JBL 2414H-C
Input Connectors:	1 × Neutrik® Speakon® NL4MP
Enclosure Construction:	Trapezoid, 15 mm, MDF

¹ Full space (4π) conditions


² Calculated maximum SPL based on rated power handling

³ IEC standard, pink noise with 6 dB crest factor for 2 hours


JBL continually engages in research related to product improvement. Some materials, production methods and design refinements are introduced into existing products without notice as a routine expression of that philosophy. For this reason, any current JBL product may differ in some respect from its published description, but will always equal or exceed the original design specifications unless otherwise stated.

▶ MTS10 10-Inch Full Range Loudspeaker System

Frequency Response:




Beamwidth:



Dimensions:

Dimensions in mm



JBL Professional
 8500 Balboa Boulevard, P.O. Box 2200
 Northridge, California 91329 U.S.A.
 © Copyright 2018 JBL Professional
 www.jblpro.com